



Compact Fans - All Metal

AC Axial

Model	Bearing	Voltage (VAC)	Frequency (Hz)	Current (mA)	Speed (RPM)	Watt (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
120 x 120 x 38 mm - Metal									
12A230HBAC-M	Ball	230	50/60	100/90	2700/3100	17/15	95/107	8.4/9.4	42/46
172 x 150 x 55 mm - Metal									
17A230HBAC-M	Ball	230	50/60	250/230	2800/3250	42/42	195/230	14/16	49/53
225 x 225 x 80 mm - Metal									
225A230HBAC-M	Ball	230	50/60	400/425	2500/2800	80/85	530/600	17/14	59/61
280 x 280 x 80 mm - Metal									
280A230HBAC-M	Ball	230	50/60	590/820	2500/2700	119/130	1090/1130	16.5/20	68/70

Also available 115VAC & 415VAC

DC Brushless


Model	Bearing*	Voltage (VDC)	Current (mA)	Speed (RPM)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
225 x 225 x 80 mm - Metal							
225A48HBDC - M	Ball	48	1100	2850	647	25	67
280 x 280 x 80 mm - Metal							
280A48HBDC - M	Ball	48	1900	2700	1130	22	69

Specifications subject to change without notice

Accessories



Plastic Finger Guards



Metal Finger Guards - Chrome & Powder Coated



Filter Kits