



Compact Fans - DC Brushless

Model	Bearing*	Voltage (VDC)	Current (mA)	Speed (RPM)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
60X60X20mm (Also available 60X60X25mm)							
6P12HSDC	Sleeve	12	180	4300	18	3.8	30
6P24HSDC	Sleeve	24	125	4300	18	3.8	30
80X80X25mm (Available upto 58 CFM)							
8P12HBDC	Ball	12	200	3000	38	4.5	34
8P24HBDC	Ball	24	150	3000	38	4.5	34
8P48HBDC	Ball	48	70	3000	38	4.5	34
92X92X25mm (Available upto 65 CFM)							
9P12HBDC	Ball	12	300	2500	55	5	40
9P24HBDC	Ball	24	200	2500	55	5	40
9P48HBDC	Ball	48	100	3000	55	5	40
120X120X38mm							
12P12HBDC	Ball	12	350	3000	105	8	48
12P24HBDC	Ball	24	250	3000	105	8	48
12P48HBDC	Ball	48	105	3000	105	8	48
12P48H1BDC (190CFM)	Ball	48	400	4200	192	17.1	54.6
12P48H1BDC(240CFM)	Ball	48	1330	5500	285	47.1	69.5
172x150x51mm & 172x172x55mm (Available upto 282CFM)							
17A12HBDC	Ball	12	1600	3000	210	13	58
17A24HBDC	Ball	24	750	3000	210	13	58
17A48HBDC	Ball	48	450	3000	210	13	58

Additional Features - Fan Failure Alarm ■ Alarm Signal For Speed Monitoring ■ PWM ■ Higher Air Flow ■ Non-standard voltages